

CLBV555

Quality Load Banks
at a Good Price



Hot air exhaust.

Rugged, lightweight aluminum construction to ensure no rusting. (Optional casters and lift channels also shown.)


Cold air inlet.

High-performance blower to ensure that the resistors do not overheat.

Recessed control panel with master and fan switches, step switches, digital meter and warning lamps.

Recessed auxiliary plug panel with various optional plugs shown (120V, Auto-Load-Dump, 3 ph blower)

Recessed power connection panel with 400 amp cam-lock connectors. (Optional cover not shown.)



**General
Platinum**
LOAD BANKS

Pittsburgh, PA • USA
generalplatinum.com
info@generalplatinum.com




CLBV555

Quality Load Banks
at a Good Price

CERTIFICATION	Product will have the CSA label "US Field Evaluation for Electrical Products".
CONSTRUCTION	The structure is all-aluminum to ensure no corrosion. Heavy-duty skeleton frame holds panels and equipment in place.
RESISTORS	The resistors are a stainless steel alloy to ensure long-life and a minimum change in resistance from cold to hot.
SAFETY	Ground terminal is provided. Blower inlet is shielded. Thermal and air pressure cutouts ensure that equipment does not exceed permissible temperatures.
CONNECTIONS	Customer connects the power to the load bank via heavy-duty 400 amp industry-standard connectors. Auxiliary power is provided through a flanged male receptacle. An optional connection is via a serial port to the digital meter to record the test session.
CONTROLS	The controls are in a recessed panel to prevent accidental damage. Master switch turns the unit and the meter display on. A fan switch turns the blower on and enables the load steps. Individual step switches allow power to be added in increments. A "load-enable" switch allows the load to be set first and then instantly loaded to the generator.
OPTIONS	Available options are: 5" casters, lift channels / tie-down points, digital recording capability, auto-load-dump, 120V aux power, 3 ph aux power.
ACCESSORIES	Available accessories are: vinyl transport cover, exhaust cover, controls cover, camlock cover, aux power cover.

PRODUCT	KW	VOLTAGE	STEPS	DIMENSIONS
CLBV395-SV	395	600	5/10/20/40/4x80	60x33x59H
CLBV395-DV	395	600/480	5/10/20/40/4x80	
CLBV395-MV	395	600/480/240/208	5/10/20/40/4x80	
CLBV555-SV	555	600	5/10/20/40/80/4x100	79x45x88H
CLBV555-DV	555	600/480	5/10/20/40/80/4x100	
CLBV555-MV	555	600/480/240/208	5/10/20/40/80/4x100	
CLBV655-SV	655	600	5/10/20/40/80/5x100	79x45x88H
CLBV655-DV	655	600/480	5/10/20/40/80/5x100	
CLBV655-MV	655	600/480/240/208	5/10/20/40/80/5x100	
CLBV755-SV	755	600	5/10/20/40/80/6x100	79x45x88H
CLBV755-DV	755	600/480	5/10/20/40/80/6x100	
CLBV755-MV	755	600/480/240/208	5/10/20/40/80/6x100	



**General
Platinum**
LOAD BANKS

Pittsburgh, PA • USA
generalplatinum.com
info@generalplatinum.com



CLBV555 • 02/21