

# CLBX1555

Quality Load Banks  
at a Good Price

Rugged,  
lightweight  
aluminum  
construction  
to ensure no  
rusting.


Recessed control  
panel with master and  
fan switches, step  
switches, digital meter  
and warning lamps.



Recessed auxiliary  
plug panel with  
various optional  
plugs shown (120V,  
Auto-Load-Dump,  
3 ph blower)

High-performance  
blower to ensure  
that resistors do  
not overheat.

Recessed power  
connection panel  
with 400 amp  
cam-lock connectors.  
Optional cover not  
shown.



**General  
Platinum**  
LOAD BANKS

Pittsburgh, PA • USA  
[generalplatinum.com](http://generalplatinum.com)  
[info@generalplatinum.com](mailto:info@generalplatinum.com)




# CLBX1555

Quality Load Banks  
at a Good Price

<b>CERTIFICATION</b>	Product will have the CSA label "US Field Evaluation for Electrical Products".
<b>CONSTRUCTION</b>	The structure is all-aluminum to ensure no corrosion. Heavy-duty skeleton frame holds panels and equipment in place.
<b>RESISTORS</b>	The resistors are a stainless steel alloy to ensure long-life and a minimum change in resistance from cold to hot.
<b>SAFETY</b>	Ground terminal is provided. Blower inlet is shielded. Thermal and air pressure cutouts ensure that equipment does not exceed permissible temperatures.
<b>CONNECTIONS</b>	Customer connects the power to the load bank via heavy-duty 400 amp industry-standard connectors. Auxiliary power is provided through a flanged male receptacle. An optional connection is via a serial port to the digital meter to record the test session.
<b>CONTROLS</b>	The controls are in a recessed panel to prevent accidental damage. Master switch turns the unit and the meter display on. A fan switch turns the blower on and enables the load steps. Individual step switches allow power to be added in increments. A "load-enable" switch allows the load to be set first and then instantly loaded to the generator.
<b>OPTIONS</b>	Available options are: lift channels / tie-down points, digital recording capability, auto-load-dump, 120V aux power, 3 ph aux power.
<b>ACCESSORIES</b>	Available accessories are: vinyl transport cover, inlet cover, exhaust cover, controls cover, camlock cover, aux power cover.

PRODUCT	KW	VOLTAGE	STEPS	DIMENSIONS
CLBX1155-SV	1155	600	5/10/20/40/80/10x100	78x84x52H
CLBX1155-DV	1155	600/480	5/10/20/40/80/10x100	
CLBX1155-MV	1155	600/480/240/208	5/10/20/40/80/10x100	
CLBX1355-SV	1355	600	5/10/20/40/80/12x100	84x88x54H
CLBX1355-DV	1355	600/480	5/10/20/40/80/12x100	
CLBX1355-MV	1355	600/480/240/208	5/10/20/40/80/12x100	
CLBX1555-SV	1555	600	5/10/20/40/80/14x100	84x88x54H
CLBX1555-DV	1555	600/480	5/10/20/40/80/14x100	
CLBX1555-MV	1555	600/480/240/208	5/10/20/40/80/14x100	



**General  
Platinum**  
LOAD BANKS

Pittsburgh, PA • USA  
generalplatinum.com  
info@generalplatinum.com



CLBX1555 • 12/20