

CLBX955

Quality Load Banks
at a Good Price

Rugged, lightweight aluminum construction to ensure no rusting.


Recessed control panel with master and fan switches, step switches, digital meter and warning lamps.



Recessed auxiliary plug panel with various optional plugs shown (120V, Auto-Load-Dump, 3 ph blower)

High-performance blower to ensure that resistors do not overheat.

Recessed power connection panel with 400 amp cam-lock connectors. Optional cover not shown.



**General
Platinum**
LOAD BANKS

Pittsburgh, PA • USA
generalplatinum.com
info@generalplatinum.com




CLBX955

Quality Load Banks
at a Good Price

CERTIFICATION	Product will have the CSA label "US Field Evaluation for Electrical Products".
CONSTRUCTION	The structure is all-aluminum to ensure no corrosion. Heavy-duty skeleton frame holds panels and equipment in place.
RESISTORS	The resistors are a stainless steel alloy to ensure long-life and a minimum change in resistance from cold to hot.
SAFETY	Ground terminal is provided. Blower inlet is shielded. Thermal and air pressure cutouts ensure that equipment does not exceed permissible temperatures.
CONNECTIONS	Customer connects the power to the load bank via heavy-duty 400 amp industry-standard connectors. Auxiliary power is provided through a flanged male receptacle. An optional connection is via a serial port to the digital meter to record the test session.
CONTROLS	The controls are in a recessed panel to prevent accidental damage. Master switch turns the unit and the meter display on. A fan switch turns the blower on and enables the load steps. Individual step switches allow power to be added in increments. A "load-enable" switch allows the load to be set first and then instantly loaded to the generator.
OPTIONS	Available options are: 5" casters, lift channels / tie-down points, digital recording capability, auto-load-dump, 120V aux power, 3 ph aux power.
ACCESSORIES	Available accessories are: vinyl transport cover, inlet cover, exhaust cover, controls cover, camlock cover, aux power cover.

PRODUCT	KW	VOLTAGE	STEPS	DIMENSIONS
CLBX755-SV	755	600	5/10/20/40/80/6x100	84x46x54H
CLBX755-DV	755	600/480	5/10/20/40/80/6x100	
CLBX755-MV	755	600/480/240/208	5/10/20/40/80/6x100	
CLBX955-SV	955	600	5/10/20/40/80/8x100	63x74x48H
CLBX955-DV	955	600/480	5/10/20/40/80/8x100	
CLBX955-MV	955	600/480/240/208	5/10/20/40/80/8x100	
CLBX1155-SV	1155	600	5/10/20/40/80/10x100	78x84x52H
CLBX1155-DV	1155	600/480	5/10/20/40/80/10x100	
CLBX1155-MV	1155	600/480/240/208	5/10/20/40/80/10x100	



**General
Platinum**
LOAD BANKS

Pittsburgh, PA • USA
generalplatinum.com
info@generalplatinum.com



CLBX955 • 12/20