





Pittsburgh, PA • USA generalplatinum.com info@generalplatinum.com



CERTIFICATION	Product will have the CSA label "US Field Evaluation for Electrical Products".		
CONSTRUCTION	The structure is all-aluminum to ensure no corrosion. Heavy-duty skeleton frame holds panels and equipment in place.		
RESISTORS	The resistors are a stainless steel alloy to ensure long-life and a minimum change in resistance from cold to hot.		
SAFETY	Ground terminal is provided. Fan inlets are shielded. Thermal and air pressure cutouts ensure that equipment does not exceed permissible temperatures.		
CONNECTIONS	Customer connects the power to the load bank via heavy-duty 400 amp industry-standard connectors. Control power is connected through a flanged male receptacle. An optional connection is via a comms port to the digital meter to record the test session.		
CONTROLS	The controls are in a recessed panel to prevent accidental damage. Master switch turns the unit and the meter display on. A fan switch turns the fans on and enables the load steps. Individual step switches allow power to be added in increments. A "load-enable" switch allows the load to be set first and then instantly loaded to the generator.		
OPTIONS	Available options are: 3" casters, lift channels / tie-down points, digital recording capability.		
ACCESSORIES	Available accessories are: shipping crate with or without casters, vinyl cover.		

PRODUCT	KW	VOLTAGE	STEPS	DIMENSIONS
CLBZ35-SV	35	600	5/10/20	23x19x19H
CLBZ35-DV	35	600/480	5/10/20	
CLBZ35-MV	35	600/480/240/208	5/10/20	
CLBZ55-SV	55	600	5/10/20/20	23x19x27H
CLBZ55-DV	55	600/480	5/10/20/20	
CLBZ55-MV	55	600/480/240/208	5/10/20/20	
CLBZ95-SV	95	600	5/10/20/20/40	23x19x35H
CLBZ95-DV	95	600/480	5/10/20/20/40	
CLBZ95-MV	95	600/480/240/208	5/10/20/20/40	
CLBX155-SV	155	600	5/10/20/40/80	50x28x32H
CLBX155-DV	155	600/480	5/10/20/40/80	
CLBX155-MV	155	600/480/240/208	5/10/20/40/80	



Pittsburgh, PA • USA generalplatinum.com info@generalplatinum.com

