

LBX255

Quality Load Banks
at a Good Price


Rugged, lightweight aluminum construction to ensure no rusting. (optional casters and lift channels also shown)

Recessed control panel with master and fan switches, step switches, digital meter and warning lamps.

Recessed auxiliary plug panel with various optional plugs shown (120V, Auto-Load-Dump, 3 ph blower)

High-performance blower to ensure that resistors do not overheat.

Recessed power connection panel with 400 amp cam-lock connectors. Optional cover not shown.



**General
Platinum**
LOAD BANKS

Pittsburgh, PA • USA
generalplatinum.com
info@generalplatinum.com



LBX255

Quality Load Banks
at a Good Price

CONSTRUCTION

The structure is all-aluminum to ensure no corrosion.
Heavy-duty skeleton frame holds panels and equipment in place.

RESISTORS

The resistors are a stainless steel alloy to ensure long-life and a minimum change in resistance from cold to hot.

SAFETY

Ground terminal is provided. Blower inlet is shielded. Thermal and air pressure cutouts ensure that equipment does not exceed permissible temperatures.

CONNECTIONS

Customer connects the power to the load bank via heavy-duty 400 amp industry-standard connectors. Auxiliary power is provided through a flanged male receptacle. An optional connection is via a serial port to the digital meter to record the test session.

CONTROLS

The controls are in a recessed panel to prevent accidental damage. Master switch turns the unit and the meter display on. A fan switch turns the blower on and enables the load steps. Individual step switches allow power to be added in increments. A "load-enable" switch allows the load to be set first and then instantly loaded to the generator.


OPTIONS

Available options are: 5" casters, lift channels / tie-down points, digital recording capability, auto-load-dump, 120V aux power, 3 ph aux power.

ACCESSORIES

Available accessories are: vinyl transport cover, inlet cover, exhaust cover, controls cover, camlock cover, aux power cover.

PRODUCT	KW	VOLTAGE	STEPS	DIMENSIONS
LBX155-SV	155	480 or 240	5/10/20/40/80	50x28x33H
LBX155-DV	155	480/240/208	5/10/20/40/80	
LBX155-MV	155	600/480/240/208	5/10/20/40/80	
LBX255-SV	255	480 or 240	5/10/20/40/80/100	59x30x36H
LBX255-DV	255	480/240/208	5/10/20/40/80/100	
LBX255-MV	255	600/480/240/208	5/10/20/40/80/100	
LBX395-SV	395	480 or 240	5/10/20/40/80x4	61x34x43H
LBX395-DV	395	480/240/208	5/10/20/40/80x4	
LBX395-MV	395	600/480/240/208	5/10/20/40/80x4	



**General
Platinum**
LOAD BANKS

Pittsburgh, PA • USA
generalplatinum.com
info@generalplatinum.com



LBX255 • 10/20