





Pittsburgh, PA • USA generalplatinum.com info@generalplatinum.com



CONSTRUCTION	The structure is all-aluminum to ensure no corrosion. Heavy-duty skeleton frame holds panels and equipment in place.
RESISTORS	The resistors are a stainless steel alloy to ensure long-life and a minimum change in resistance from cold to hot.
SAFETY	Ground terminal is provided. Fan inlets are shielded. Thermal cutouts ensure that equipment does not exceed permissible temperatures.
CONNECTIONS	Customer connects the power to the load bank via heavy-duty 400 amp industry-standard connectors. Control power is connected through a flanged male receptacle. An optional connection is via a comms port to the digital meter to record the test session.
CONTROLS	The controls are in a recessed panel to prevent accidental damage. Master switch turns the unit and the meter display on. A fan switch turns the fans on and enables the load steps. Individual step switches allow power to be added in increments. A "load-enable" switch allows the load to be set first and then instantly loaded to the generator.
OPTIONS	Available options are: 5" casters, lift channels / tie-down points, digital recording capability.
ACCESSORIES	Available accessories are: shipping crate with or without casters, vinyl cover.

PRODUCT	KW	VOLTAGE	STEPS	DIMENSIONS
LBZ95-SV	95	480 or 240	5/10/4x20	23x19x35H
LBZ95-DV	95	480/240/208	5/10/4×20	
LBZ95-MV	95	600/480/240/208	5/10/4x20	
LBZ155-SV	155	480 or 240	5/10/20/3x40	26x47x44H
LBZ155-DV	155	480/240/208	5/10/20/3x40	
LBZ155-MV	155	600/480/240/208	5/10/20/3x40	
LBZ235-SV	235	480 or 240	5/10/20/5x40	26x63x44H
LBZ235-DV	235	480/240/208	5/10/20/5x40	
LBZ235-MV	235	600/480/240/208	5/10/20/5x40	
LBZ315-SV	315	480 or 240	5/10/20/40/3x80	26x63x60H
LBZ315-DV	315	480/240/208	5/10/20/40/3x80	
LBZ315-MV	315	600/480/240/208	5/10/20/40/3x80	



Pittsburgh, PA • USA generalplatinum.com info@generalplatinum.com

